

NOARK

UVT11NCD

Undervoltage (U/V) trip release coil - 1801010 - 2500A frame - for 2500A ACB/switch disconnector

Undervoltage (U/V) trip release coil - for A25/ASD25 (2500A) frame size - NOARK (A25 series) - 94-143Vdc (110Vdc-130Vdc nom.) / 94-143Vac (110Vac-130Vac nom.) control voltage - equivalent to 1801010

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Coil (Tripping)
Product series / family name	Electrical protection > ACBs and disconnector switches accessories > Auxiliary controls
Sub-range name	A25 series
Functions	Undervoltage (U/V) trip release coil
Control Voltage (AC)	94-143Vac (110Vac-130Vac nom.) 33-78Vac (dropout voltage; below this voltage coil will always trip the MCCB)
Control Voltage (DC)	94-143Vdc (110Vdc-130Vdc nom.) 33-78Vdc (drop-out voltage; below this voltage coil will always trip the MCCB)
Response time	(operating time) max. 70ms / 0.07 s
Power consumption	(inrush) 500 W (continuous) 4.5 W
Technical compatibility with	for A25/ASD25 (2500A) frame size
Power consumption	(inrush) 500 VA (continuous) 4.5 VA
Order code / Manufacturer SKU	UVT11NCD 1801010
Manufacturer product status	Commercialized
Equivalent to	1801010

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Documents

NOARK - Power Circuit Breakers and Non-Automatic Switches - Catalog.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com