

NOARK

UVT22NH

Undervoltage (U/V) trip release coil - 1100544 - 220Vdc-250Vdc

Undervoltage (U/V) trip release coil - for M2 / M3 frame size - NOARK - 220Vdc-250Vdc control voltage - equivalent to 1100544

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Coil (Tripping)
Product series / family name	Electrical protection > MCCBs and disconnector switches accessories > Auxiliary controls
Functions	Undervoltage (U/V) trip release coil
Control Voltage (DC)	220Vdc-250Vdc 187-275Vdc (pick-up voltage) / 77-175Vdc (dropout voltage; below this voltage coil will always trip the MCCB)
Response time	(operating time) 10-60ms / 0.01-0.06 s
Dimensions	H46.5mm x W36.8mm x D32mm H1.83" x W1.45" x D1.26"
Technical compatibility with	for M2 / M3 frame size
Order code / Manufacturer SKU	UVT22NH 1100544
Manufacturer product status	Commercialized
Equivalent to	1100544
Compliant with standard(s)	UL489 listed (file number E355392) CSA C22.2 No.5 IEC/EN 60947-2 CE marking RoHS compliant

Documents

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

UVT22NH

Undervoltage (U/V) trip release coil - 1100544 - 220Vdc-250Vdc

NOARK - MCCB MCP MCS Ex9 series-M - Catalog.pdf

Access to all NOARK drawings

E-PLAN - NOARK - UVT22NH - Part details

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com