


NOARK

UVT3110NB

Undervoltage trip coil UL489 - 1001205 - 1NO - 48Vac/dc

Undervoltage trip release coil - for UL489 devices - NOARK - 48Vac / 48Vdc control voltage - 1NO (1 Normally Open) aux. contacts - DIN rail mounting (35mm width) - equivalent to 1001205

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Coil (Tripping)
Product series / family name	Electrical protection > MCBs accessories > UL489 > Trip coils > Undervoltage trip
Functions	Undervoltage trip release coil
Design	for UL489 devices
Cross-section	for #18AWG...#14AWG / 0.5mm2...4mm2 Cu wires at 140/167°F / 60/75°C
Control Voltage (AC)	48Vac
Control Voltage (DC)	48Vdc
Mounting mode	DIN rail
Normally Open (NO) auxliary contacts	1 NO contacts
Contacts type	1NO (1 Normally Open) aux. contacts
Dimensions	H103.1mm x W17.8mm x D75.4mm 7mm / 0.3" reference stripping length H4.06" x W0.7" x D2.97"
Net Width (mm)	35 mm
Order code / Manufacturer SKU	UVT3110NB 1001205
Manufacturer product status	Commercialized
Equivalent to	1001205

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Compliant with standard(s)	UL 489
Tightening torque	9lb.in / 1 N.m
Application type	Branch Circuit Protection - Convenience receptacle circuits (internal/external) - Motor control circuits - Load circuits leaving the equipment (external) - HVACR equipment -- heating / ventilation / air conditioning / refrigeration (internal/external) - PLC I/O points - Power supplies - Control instrumentation - Relays - UPS - Power conditioners

Documents

NOARK - DIN Rail Miniature Circuit Breakers - Ex9 B1 series - Datasheet.pdf

Access to all NOARK drawings

E-PLAN - NOARK - UVT3110NB - Part details

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com