


NOARK

UVT31NC

Undervoltage trip coil UL489 - 1002577 - 12-24Vac/dc

Undervoltage trip release coil - for UL489 devices - NOARK - 12Vac-24Vac / 12Vdc-24Vdc control voltage - DIN rail mounting (35mm width) - equivalent to 1002577

Additional information

The technical information provided in the datasheet is subject to change without notice. For confirmation, please contact NOARK's product support team.

Specifications

Primary brand	NOARK
Main function	Coil (Tripping)
Product series / family name	Electrical protection > MCBs accessories > UL489 > Trip coils > Undervoltage trip
Functions	Undervoltage trip release coil
Design	for UL489 devices
Cross-section	for #18AWG...#14AWG / 0.5mm2...4mm2 Cu wires at 140/167°F / 60/75°C
Control Voltage (AC)	12Vac-24Vac
Control Voltage (DC)	12Vdc-24Vdc
Mounting mode	DIN rail
Dimensions	H103.1mm x W17.8mm x D75.4mm 7mm / 0.3" reference stripping length H4.06" x W0.7" x D2.97"
Net Width (mm)	35 mm
Order code / Manufacturer SKU	UVT31NC 1002577
Manufacturer product status	Commercialized
Equivalent to	1002577
Compliant with standard(s)	UL 489
Tightening torque	9lb.in / 1 N.m

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com

Documents

NOARK - DIN Rail Miniature Circuit Breakers - Ex9 B1 series - Datasheet.pdf

Access to all NOARK drawings

All rights reserved 2016-2026 to KYKLO and products.na.noark-electric.com