


BUS DROP GRIPS

Bus Drop Grips support flexible cord or cable when supplying power from an overhead source. They relieve tension and absorb vibration, protecting the cable.




* Made of galvanized steel

Cable Range	Part #	Description	Approx.* Breaking Strength	Length	
				Eye	Mesh
Single Eye—Wide Range					
.22- .32	7304-001	BD022	1100	3	3-1/2
.30- .43	7304-002	BD030	1100	4	4-1/2
.41- .56	7304-003	BD041	1100	6	5
.53- .73	7304-004	BD053	1100	7	6-1/2
.70- .85	7304-005	BD070	1900	7	8-1/2
.82-1.00	7304-006	BD082	1900	8	8-1/2
.96-1.25	7304-007	BD096	1900	9	11
Universal Bail—Wide Range					
.22- .32	7304-009	BD022-UB	1100	12	3-1/2
.30- .43	7304-010	BD030-UB	1100	12	4-1/2
.41- .56	7304-011	BD041-UB	1100	12	5
.53- .73	7304-012	BD053-UB	1100	15	6-1/2
.70- .85	7304-013	BD070-UB	1900	16	8-1/2
.82-1.00	7304-014	BD082-UB	1900	16	8-1/2
.96-1.25	7304-015	BD096-UB	1900	17	11



Single Eye



Universal Bail

BUS DROP SAFETY SPRINGS

Safety Springs relieve sudden stress on cord or cable overhead systems when used with Bus Drop Grips. Springs can be used with Single Eye type grips by disassembling drawbar from coil, placing through eye and replacing drawbar.

Description	Part #	Maxium Deflection	Approx.* Breaking Strength	Length No Load	Diameter
40 lb. Spring	203-02-001	2-5/8" at 40 lbs.	500	8-1/4"	3/4"
80 lb. Spring	203-02-002	3-1/8" at 80 lbs.	850	8-1/4"	1"

